



Betriebsmodi fuer 68HC11 :

MODB	MODA	
GND	GND	special bootstrap
GND	VCC	special test
VCC	GND	single chip
VCC	VCC	expanded multiplexed

Pinout for IC11A:

Pin	Signal	Pin	Signal
1	SCK	66	OVCC
2	MOSI	65	OUT7
3	MISO	64	OUT6
4	OUT8	63	OUT5
5	OUT9	62	OUT4
6	OUT10	61	OUT3
7	OUT11	60	OUT2
8	OUT12	59	OUT1
9	A15	58	OUT0
10	A14	57	PE7
11	A13	56	PE6
12	A12	55	PE5
13	A11	54	PE4
14	A10	53	PE3
15	A9	52	PE2
16	A8	51	PE1
17	A7	50	PE0
18	A6	49	EXTE
19	A5	48	PA0
20	A4	47	PA1
21	A3	46	PA2
22	A2	45	PA3
23	A1	44	PA4
24	A0	43	PA5
25	D7	42	PA6
26	D6	41	PA7
27	D5	40	PD5
28	D4	39	IRQ*
29	D3	38	E
30	D2	37	R/W
31	D1	36	RESET*
32	D0	35	TXD
33	GND	34	RXD

Bei Einsatz der RTC koennen PA3 u. PA4 nur noch eingeschraenkt verwendet werden

RAM oder EPROM
 RAM (32Kx8) J7 2-3; J6 1-2
 EPROM (32Kx8) J7 1-2; J6 2-3